GRADING, DRAINAGE, AND ROAD CONSTRUCTION PLANS


MISSOULA LOFT HOMES ON MARY JANE LOCATED IN SECTION 18, T13N, R19W, P.M.M., MISSOULA COUNTY, MONTANA






DESCRIPTION SHEET NO. SHEET 2 OF 20 LEGEND AND NOTES SHEET SHEET 3-4 OF 20 BOAD PLAN & PROFILE SHEET (BOAD "A" / KILLARNEY) SHEET 4 OF 20 ROAD PLAN & PROFILE SHEET (GEARY) SHEET 5 OF 20 SHEET 6 OF 20 ROAD PLAN & PROFILE SHEET (O'LEARY) SHEET 6-7 OF 20 ROAD PLAN & PROFILE SHEET (MARY JANE) SHEET 8 OF 20 PARK GRADING PLAN SHEET 9 OF 20 BOULEVARD TREE PLAN **SHEET 10 OF 20** BOULEVARD TREE PLAN BOULEVARD TREE PLAN SHEET 12 OF 20 SIGNAGE AND STRIPING PLAN SHEET 13 OF 20 SIGNAGE AND STRIPING PLAN SHEET 14 OF 20 DRY UTILITY PLAN **SHEET 15 OF 20** DRY UTILITY PLAN SHEET 16 OF 20 SWPP & MASS GRADING PLAN SHEET 17 OF 20 SWPP & MASS GRADING PLAN SHEET 18 OF 20 SHEET 19 OF 20 ROAD CROSS SECTIONS SHEET 20 OF 20 DETAIL SHEET SHEET D1 OF D9 DETAIL SHEET SHEET D2 OF D9 DETAIL SHEET SHEET D3 OF D9 DETAIL SHEET SHEET D4 OF D9 DETAIL SHEET SHEET D5 OF D9 DETAIL SHEET SHEET D6 OF D9 DETAIL SHEET SHEET D7 OF D9 DETAIL SHEET SHEET D8 OF D9

SHEET INDEX





MISSOULA, MISSOULA COUNTY




CHECKED: XX


ROAD

AGENCIES REVIEW STATUS: CITY OF MISSOULA DEV. SERVICES PLAN SET IS READY FOR CONSTRUCTION

PROJECT STATUS

PROJECT NOTES: MISSOULA CITY PUBLIC WORKS STANDARDS & SPECIFICATIONS (MCPWSS) EDITION JAN. 2023





GENERAL CONDITIONS OF CONSTRUCTION:

- The Standard General Conditions of the Contract prepared by the Engineers Joint Contract Documents Committee (Copyright 2007), as included in Montana Public Works Standard Specifications, are herein referred to as the General Conditions within
- these Drawings. Copies of the General Conditions will be provided to Contractor upon written request to Engineer.

 Wherever used in these Drawings, the terms, whether printed with initial capital letters or not, as listed in the Standard General Conditions of the Construction Contract (General Conditions), Article 1 - Definitions and Terminology, prepared by the Engineers Joint Contract Documents Committee (Copyright 2007) will have the meanings indicated, which are applicable to both the singular and plural thereof, except as follows:
 - a. The Contract Documents shall mean the Drawings as shown in these plans and any applicable referenced standards specifications, or laws.
 - b. The Contract Price shall mean the moneys payable by Owner to Contractor for completion of the Work in accordance with
 - c. The Contract Times shall mean the number of days or the dates stated in the Agreement to complete the Work so that it
 - is ready for final payment. If no such dates are established, the Contract Time shall be 120 days to complete the Work. Effective Date of the Agreement shall have the meaning as listed in the General Conditions, Article 1. If no such Agreement exists, the Effective Date of the Agreement shall be the day the Contractor proceeds with the Work.
- 3. By proceeding with the Work as shown on these Drawings, the Contractor makes the following representations
 - . Contractor has examined and carefully studied the Drawings and other related data. b. Contractor is familiar with and is satisfied as to all federal, state and local laws and Regulations that may affect cost.
 - progress, performance and furnishing of the Work.

 Contractor has visited the site and become familiar with and is satisfied as to the general, local and Site conditions that
 - may affect cost, progress, performance or furnishing of the Work.
 - d. Contractor acknowledges that Owner and Engineer do not assume responsibility for the accuracy or completeness of mation and data shown or indicated in the Drawings with respect to Underground Facilities at or contiguous to the
 - e. Contractor has obtained and carefully studied (or assumes responsibility for having done so) all such additional supplementary examinations, investigations, explorations, tests, studies and data concerning conditions (surface, subsurface and Underground Facilities) at or contiguous to the site or otherwise, which may affect cost, progress, performance or furnishing of the Work or which relate to any aspect of the means, methods, techniques, sequences and procedures of construction to be employed by Contractor including applying the specific means, methods, techniques, sequences and procedures of construction, if any, expressly required by the Drawings to be employed by the Contractor and safety precautions and programs incident thereto.
 - f. Contractor is aware of the general nature of work to be performed by Owner and others at the site that relates to the
 - g. Contractor has given Engineer written notice of all conflicts, errors, ambiguities or discrepancies that Contractor has discovered in the Drawings and the written resolution thereof by Engineer is acceptable to Contractor
- h. The Drawings are generally sufficient to indicate and convey understanding of all terms and conditions for performance
- In resolving disputes resulting from conflicts, errors or discrepancies, the order of precedence shall be as follows, as applicable
- to this project: Written agreement between owner and contractor, specifications, Drawings, Within the Specifications, the order of precedence is as follows, as applicable to this project: Addenda/Change Orders, Contractor's Bid, Special Provisions, Instructions to Bidders, Supplemental General Conditions, Notice Inviting Bids, General Conditions, Technical Specifications Referenced Standard Specifications. With reference to the Drawings, the order of precedence is as follows, as applicable to this project: Figures govern over scaled dimensions, Detail drawings govern over general drawings, Addenda/Change Order drawings govern over contract drawings, contract drawings govern over standard drawings, contract drawings govern over shop drawings.
- 5. If Contractor believes that any subsurface or physical condition at or contiguous to the Site that
 - . is uncovered or revealed either is of such a nature as to require a change in the Drawings; or . differs materially from that shown or indicated in the Drawings; or

 - c. is of an unusual nature, and differs materially from conditions ordinarily encountered and generally recognized as inherent

in work of the character provided in the drawings;
then Contractor shall promptly after becoming aware thereof and before further disturbing the subsurface or physical conditions or performing any Work in connection therewith (except in an emergency), notify Owner and Engineer in writing about such condition. Contractor shall not further disturb such condition or perform any Work in connection therewith (except as aforesaid) until receipt of written order to do so.

- Section 2.06 of the General Conditions is hereby incorporated into these Drawings.
- Section 3.03.A.2 of the General Conditions is hereby incorporated into these Drawings
- Section 3.05 of the General Conditions is hereby incorporated into these Drawings. Section 3.06 of the General Conditions is hereby incorporated into these Drawings.
- 10. Section 4.05 of the General Conditions is hereby incorporated into these Drawings
- Section 6.01, 6.02.A, and 6.03 of the General Conditions are hereby incorporated into these Drawings. Substitutes and "Or-Equals" items are subject to the provisions of the General Conditions, Section 6.03
- 13. Section 6.13 of the General Conditions is hereby incorporated into these Drawings, except that Section 6.13.D shall be replaced with the following sentence.
- Contractor's duties and responsibility for safety and for protection of the Work shall continue until such time as all the
- Work is completed and Engineer and Owner, as applicable to the Work, have accepted that the work is complete.

 14. Section 6.11, 6.14, 6.15, 6.16, 6.18, 6.19, 6.20, and 6.21 of the General Conditions are hereby incorporated into these Drawings.
- 15. Article 9 Engineer's Status During Construction of the General Conditions is hereby incorporated into these Drawings, excep
 - a. Delete the last sentence of Section 9.05.A.
- b. Delete Section 9.06, 9.07, 9.08.B, 9.08.C, and 9.09.D.
 Section 10.02 of the General Conditions is hereby incorporated into these Drawings.
 Article 13 Tests and Inspections, Correction, Removal or Acceptance of Defective Work of the General Conditions is hereby incorporated into these Drawings.

STANDARD SPECIAL PROVISIONS:

- 1. The Contractor shall be responsible for all permits, licenses and fees required for completion of this project unless specifically
- The Contractor shall provide the Owner with a 24 hour phone number of a party responsible and capable of immediate local response to emergency maintenance for the duration of the Work. Contractor shall provide the name of the responsible party and phone number in writing prior to proceeding with the Work. Unless noted otherwise, the contractor shall be responsible for any necessary traffic control on and off-site including obtaining
- any applicable permits. erial stockpiled along the project route shall be done so in a manner that does not affect public safety and is in a neat and
- The Contractor shall be responsible for disposing of all waste and excess materials such as, but not limited to: vegetation, trees
- brush, asphalt, concrete, sub-grade soils, etc., offsite in accordance with local, state and federal laws. The Owner reserves the right to request certain waste materials to be stockpiled at a location on-site.

 The contractor will be responsible to adhere to the MDEQ or EPA approved Storm Water Pollution Prevention Plan (SWPPP), if
- applicable to the project. The contractor is responsible for repairing any damage made to BMPs identified in the SWPPP. The approved Storm Water Pollution Prevention Plan will be provided by Owner to Contractor upon written request. If a SWPPP has not been prepared for the project, but is required by regulation, the Contractor is responsible for preparing and submitting a Notice of Intent and SWPPP.
- The Contractor will be required to make every effort to immediately restore the construction area once the construction task is completed. All seeding shall be completed in accordance with MPWSS 02910. This includes such required active grading, spreading of topsoil, restoring irrigation, replacing traffic and street signs, etc. The contractor will have 48 hours to begin restoration once the construction task in the immediate area is complete. Once restoration is begun, it must be completed without interruption to the extent possible.

 After all work on this project is completed and before final acceptance of the project, the entire project shall be neatly finished to
- the lines, grades, and cross sections shown on the plans and as hereinafter specified
- a. Drainage facilities, such as inlets, catch basins, storm pipe, culverts, and curb and gutter shall be cleaned of all debris,
- gravel, silts or other foreign mate
- The Contractor shall remove and dispose of all construction stakes.
- All areas disturbed by the construction shall be shaped to present a uniform appearance blending into the contour of adjacent properties. All surface replacement and landscaping shall be completed.

 Except as otherwise permitted, all excess excavated materials shall be disposed of away from the site of the work.
- e. Broken concrete and other debris resulting from payement or sidewalk removal, excavated rock in excess of the amount permitted, and other waste and debris encountered in excavated work, and other similar waste materials shall be

There will be no separate measurement or payment for cleanup, and all costs for such work shall be included in the Contract

- No on-site burning of waste materials will be allowed.
- 10. If a street has not been surfaced and cleaned, the Contractor shall be responsible for dust control and maintenance of the street. Also, if detours are made on a gravel road, the Contractor is responsible for dust control and maintenance on the
- detours. See "Air Quality" below also.

 11. Daily street sweeping shall be completed on both ends of each street during construction. Unpaved detours or any other fugitive dust emission sources from construction and demolition should be watered and/or chemically stabilized so emissions are less than 20% opacity.

UTILITY NOTES:

- The Contractor shall notify appropriate personnel for utility locations and notice of construction commencement at least two business days prior to proceeding with the Work. Before Contractor proceeds with the Work, a common locate service (One Call' is available at 1-800-424-5555. All Underground Facilities may not be located by the One Call service including but not limited to such Underground Facilities as irrigation systems, public and private water and sewer systems, etc.
- 2. The information and data shown or indicated in the Drawings with respect to existing Underground Facilities at or contiguous to the Site is based on information and data furnished to Owner or Engineer by the owners of such Underground Facilities, including Owner, or by others. Unless it is otherwise noted:
 - a. Owner and Engineer shall not be responsible for the accuracy or completeness of any such information or date; and
 - The cost of all of the following will be included in the Contract Price, and Contractor shall have full responsibility for

 - Reviewing and checking all such information and data, Locating all Underground Facilities shown or indicated in the Drawings,
 - Coordination of the Work with the owners of such Underground Facilities, including Owner, during construction, and The safety and protection of all such Underground Facilities and repairing any damage thereto resulting from the Work. At least 2 business days before beginning any excavation, the Contractor shall, according to MCA 69-4-501, notify all
 - owners of underground facilities and coordinate the Work with the owners of such underground facilities. The information shown or indicated in the Drawings with respect to existing underground facilities is based on information and data obtained from the owners of the facilities without field exploration, and as such, Owner and Engineer are not responsible fo the accuracy or completeness of such information or data.
 - The Contractor shall support and protect all exposed utilities in conformance with the utility owner's standards
- All utility services shall be constructed per the international Plumbing Code, Local Jurisdictional policy, and the service provide standards and specifications.
- 5. All utility work shall be completed before paving.

SUBMITTALS, QUALITY CONTROL & ASSURANCE, INSPECTIONS, AND TESTING

- Contractor shall comply with Summary of Work, Section 01010, MPWSS
- Contractor shall comply with Project Coordination, Section 01041, MPWSS.
 Contractor shall comply with Field Engineering, Section 01050, MPWSS. Replace Part 1.1.A with
- "Notify Engineer of required survey work at least 5 days before starting work.
- 4. Contractor shall comply with Submittals, Section 01300, MPWSS. Contractor shall comply with the Contractor Quality Control and Owner Quality Assurance,
- as modified by MCPWSS Appendix 2-A, Section 01400.

- Contractor shall comply with Contract Closeout, Section 01700, MPWSS.

 Contractor shall comply with all Density Control Testing, Part 1.3, for Sub Base Course, Section 02234 MPWSS. This does not exclude any other requirements of Section 02234 MPWSS.
- 8. Contractor shall comply with all Density Control Testing, Part 1.3, and Materials Submittals, Part 1.4, for Crushed Base Course. Section 02235 MPWSS. This does not exclude any other requirements of Section 02235 MPWSS.

 Contractor shall comply with Pavement and Material Testing Requirements, Part 3.29, for Asphalt Concrete Pavement, Section
- 02510 MPWSS. This does not exclude any other requirements of Section 02510 MPWSS. 10. Contractor shall complete trench excavation and backfill in accordance with Section 02221 MPWSS. This includes backfill for storm
- 11. The Contractor shall coordinate with Engineer to obtain samples of trench backfill material to be used on-site. This includes backfill
- for storm drainage infrastructure. 12. Contractor will be responsible for coordination with a material testing company of the Owner's selection to complete compaction
- testing of trench backfill. Coordination includes updating appropriate personnel employed by the material testing company every work day as to progress of work so adequate testing can be completed.
- 13. The Contractor will be required to prepare a set of detailed as-built drawings to be presented to the Engineer at the completion of the project. The as-built drawings shall be updated daily and reviewed weekly by the Project Engineer. As-built drawings shall include, but not limited to location/depths of existing utilities encountered during completing the Work and location/depths of installed infrastructure completed as part of the Work. Installed infrastructure includes culverts, ponds, storm drainage systems catch basins, dry-well sumps, storm manholes, swales, ditches, dry utilities (gas, power, phone, etc.), and road and pedestriar features such as handicap ramps, sidewalks, roads, curb and gutter, etc.

CONSTRUCTION NOTES:

- All Work shall be in accordance with the Montana Public Works Standard Specifications (MPWSS), Seventh Edition, dated April 2021, City of Missoula Public Works Manual, Special Provisions, and Contract Documents, dated January, 2023.
- Contractor shall comply with Construction and Temporary Facilities, Section 01500, MPWSS.

 Contractor shall comply with Construction Traffic Control, Section 01570, MPWSS.
- 4. For road plan and profile sheets, the stationing and elevations provided are for finished grade at centerline of road, unless noted
- 5. For proposed pipe installations (culverts, storm drains, irrigation, etc.), the stationing is from centerline of pipe and elevations are rom invert of pipe, unless noted otherwise.
- Elevations shown on the Drawings are to finished surface grade unless otherwise indicated.
- Elevations for curb and gutter are for top back of curb, unless otherwise indicated. Elevations provided at curb lay downs are for the "projected" top back of curb, as though the specified curb was being installed through the lay down. This allows the contractor o set his curb string line or forms based on the elevations shown on the plans, and then cut out the extra concrete for the lay down
- 8. All material furnished on or for this project shall meet the minimum requirements of the approving agencies or as set forth herein
- 9. If more than one acre will be disturbed during construction the contractor is responsible to notify DEQ or submit Storm Water Pollution Prevention Permit (SWPPP) to DEQ prior to construction

CONSTRUCTION STAKING:

- 1. The owner will provide construction staking one time. Additional staking will be the responsibility of the contractor for scheduling
- Contractor is responsible to coordinate and request staking at least two days in advance, unless otherwise agreed upon in writing by Engineer
- Staking will be provided as indicated in the Contract Documents, or as requested by contractor
- 4. Cut sheets will be provided to the contractor with elevation from hub to finished grade, unless noted otherwise. Cut sheets for pipe installation provide the elevation from the hub to the invert of the pipe, unless noted otherwise.
- 5. Engineer does not consider staking to be complete and ready for use until cut sheets have been delivered to Contractor ractor's uses of construction staking prior to receipt of cut sheets is at contractor's risk. Any work incorrectly installed due to contractor's use of preliminary construction staking will be removed and replaced at contractor's expense

GRADING NOTES:

- 1. All ramps shall be sloped @ 12:1 max (8.33%) with a cross slope less than 2% with landings being a minimum of 5'x5' and a maximum slope in all directions of 2%. 2 Square cut all asphalt
- Contractor shall protect all adjacent improvements (buildings, roadways, fences, ditches, parking lots, utilities, sidewalks, curbs gutter, park recreation improvements, trees, etc.) from damage and erosion. All disturbed areas shall be restored to their original
- 4. Compact subgrade and gravel cushion to 95% proctor density or per geotechnical engineering report, whichever provides a greate
- STORMWATER POLLUTION PREVENTION PLAN (SWPPP)

- 1. SWPPP Administrator shall turn in SWPPP reports generated from the beginning of construction to date that As-Builts are turned into Engineer. Engineer in turn submits SWPPP reports to City Engineering as part of As-Built documentation 2. SWPPP Administrator is required to renew City SWPPP permit annually unless the site has been stabilized. SWPPP Administrator
- will submit any remaining SWPPP reports to City Engineering when filing for Notice of Terminatio

BC	ABBRI	EVIATIONS:		
BSW BACK OF SIDEWALK NWE NORTHWESTERN ENERGY	BC	BACK OF CURB	MPOC	MID POINT OF CURVE
CBU CLUSTER BOX UNIT (P)	BP	BEGINNING POINT	MUTCD	MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES
CMP	BSW	BACK OF SIDEWALK	NWE	NORTHWESTERN ENERGY
CMP CORRUGATED METAL PIPE PRC POINT OF REVERSE CURVATURE ELEV ELEVATION PC POINT OF CURVATURE EP ENDING POINT PT POINT OF TANGENT (E) EXISTING PVI POINT OF VERTICAL INTERSECTION FEL FINISHED FLOOR ELEVATION R RADIUS FG FINISHED GRADE ROW RIGHT OF WAY FL FLOWLINE SF SQUARE FOOT HP HIGH POINT SIM SIMILAR I.E. INVERT ELEVATION STA STATION INV INVERT STD CITY OF MISSOULA STANDARD DRAWING LD LAYDOWN SW SIDEWALK LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL	CBU	CLUSTER BOX UNIT	(P)	PROPOSED
EP	CMP	CORRUGATED METAL PIPE		
(E) EXISTING PVI POINT OF VERTICAL INTERSECTION FFEL FINISHED FLOOR ELEVATION R RADIUS FG FINISHED GRADE ROW HIGHT OF WAY FL FLOWLINE SF SQUARE FOOT HP HIGH POINT SIM SIMILIAR I.E. INVERT ELEVATION STA STATION INV INVERT STD CITY OF MISSOULA STANDARD DRAWING LD LAYDOWN SW SIDEWALK LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMIMIM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL	ELEV	ELEVATION	PC	POINT OF CURVATURE
FFEL FINISHED FLOOR ELEVATION R RADIUS FG FINISHED GRADE ROW RIGHT OF WAY FL FLOWLINE SF SQUARE FOOT HP HIGH POINT SIM SIMILAR I.E. INVERT ELEVATION STA STATION INV STO CITY OF MISSOULA STANDARD DRAWING LD LAYDOWN SW SIDEWALK LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL		ENDING POINT	PT	POINT OF TANGENT
FG			PVI	POINT OF VERTICAL INTERSECTION
FL			R	RADIUS
HP HIGH POINT SIM SIMILAR I.E. INVERT ELEVATION STA STATION INV INVERT STD CITY OF MISSOULA STANDARD DRAWING LD LAYDOWN SW SIDEWALK LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL			ROW	RIGHT OF WAY
I.E. INVERT ELEVATION			SF	SQUARE FOOT
INV INVERT STD CITY OF MISSOULA STANDARD DRAWING LD LAYDOWN SW SIDEWALK LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL				SIMILAR
LD LAYDOWN SW SIDEWALK LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL			STA	STATION
LF LINEAR FOOT TBC TOP BACK OF CURB MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL			STD	CITY OF MISSOULA STANDARD DRAWING
MAX MAXIMUM TOA TOP OF ASPHALT MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL				SIDEWALK
MIN MINIMUM TOC TOP OF CONCRETE M.E. MATCH EXISTING TYP TYPICAL			TBC	TOP BACK OF CURB
M.E. MATCH EXISTING TYP TYPICAL			TOA	TOP OF ASPHALT
			TOC	TOP OF CONCRETE
M.E.P. MECHANICAL, ELECTRICAL, & PLUMBING U.N.O. UNLESS NOTED OTHERWISE				
	M.E.P.	MECHANICAL, ELECTRICAL, & PLUMBING	U.N.O.	UNLESS NOTED OTHERWISE

ÄÄ 1817 MISS

DESIGNED: XX DRAFTED: D0


CHECKED: XX APR., 202


MIRAMONT


LANS إړ AND ō шì DRAINAGE END AND I SO GRADING,

20 S


NOTE: NOT ALL FEATURES SHOWN IN LEGEND WILL BE PRESENT ON PLANS








PLAN VIEW




PROFILE VIEW


DESIGNED: $\chi\chi$ DRAFTED: D0CHECKED: $\chi\chi$ APR., 2023 GRADING, DRAINAGE, AND ROAD PLANS PLAN AND PROFILE SHEET MISSOULA LOFT HOMES ON MARY JANE 20 **5** OF




PROFILE VIEW




PROFILE VIEW







9













PLAN VIEW







DATE		
REVISIONS		
DRA	IGNED: FTED: CKED:	X 10 X

AND TRACT 2 OF C.O.S. 6817 RY JANE BOULEVARD 18., T13N., R19W., P.M.M. MISSOULA COUNTY	MIRAMONTE
AND TR RY JAN 18., T13 MISSOL	MR


DATE:


APR., 2023


GRADING, DRAINAGE, AND ROAD PLANS PLAN AND PROFILE SHEET MISSOULA LOFT HOMES ON MARY JANE

20 **8** OF









NOTES:

- Plant material must meet the minimum acceptable standard set by the American Association
 of Nurserymen's American Standard of Nursery Stock: ANSI Z60.1. Broken, damaged,
 diseased, or substandard stock are prohibited from being planted in the public right-of-way
- diseased, or substandard stock are prohibited from being planted in the public right-of-way and will be rejected.

 2. Orly class I (small growing) trees are permitted to be planted under or within fifteen (15) of overhead utility lines.

 3. Prune only broken or damaged branches. Do not apply fertilizer at time of planting.

 4. The root flare is the point where the top most structural root emerges from the trunk. The depth of the root ball shall be measured from the root flare to the bottom of the root ball. Handle B&B plants carefully when transferring to planting hole.

 Lift or carry by holding the root ball, not the trunk.

 5. Remove any excess soil from the top of the root ball to expose the root flare. Place tree in planting hole with root flare level with or up to 1" above finish grade.

 6. Remove all wire baskets and rope from root ball. Be careful to keep the root ball intact.

 7. Remove all burlap from the root ball. Be careful to keep root ball lintact.

- Remove all burlap from the root ball. Be careful to keep root ball intact.
 Straighten, cut and remove any circling roots.
 Backfill planting hole 23 full with existing soil, settle with water, continue to fill with soil, water again. Water thoroughly after installation to eliminate air pockets.
 Construct a temporary raised ring of soil at dege of root ball to contain water. Remove or breach before winter.
 Construct mulch ring with a minimum 36" diameter to a depth of 2" 4"; leave 3" bare ground between mulch and tree trunk.
 Set stakes parallel to prevailing wind and outside of root ball. Ties must be 1" wide minimum, flexible belt-like strapping. Do not use rope or wire. Do not over-tighten around tree. Ties should be tight enough to support the tree while allowing it to sway. Remove stakes and ties within one year after installation.
 Trees benefit when irrigated separately from turf. Water new trees during summer months to a depth of 12" 18" once per week (about 5 gallons of water per cailper inch) for the first 3 growing seasons. During periods of drought, new trees my need more frequent watering.

ATTROUTE A	BALL AND BURLAP TREE PLANTING NOTES	
arks and Rec. Dept.	Approved by Drawn by: GLS Parks & Rec. Design Mgr. Checked by: CB Neil Miner Adopted:	


GENERAL NOTES:

- LOCATE UTILITIES BEFORE PLANTING TREES. NOTIFY MONTANA UTILITY NOTIFICATION
- CENTER (PHONE #811) PRIOR TO ANY EXCAVATION.
 TREES SHALL BE CENTERED BETWEEN BACK OF CURB AND FACE OF SIDEWALK.
- OPTIMAL TREE SPACING MAY BE MODIFIED TO ACCOMMODATE FUTURE DRIVEWAYS AND EXACT LOCATION OF UTILITIES.
- STREET TREES SHALL BE PLANTED WITHIN SIX (6) MONTHS OF COMPLETION OR OCCUPANCY OF PRIMARY STRUCTURE ERECTED ON ANY LOT, WHICHEVER OCCURS FIRST.
- BUILDER OR DEVELOPER IS RESPONSIBLE FOR INSTALLATION OF TOPSOIL AND IRRIGATION IN BOULEVARD AREA FRONTING LOTS.
- CITY OF MISSOULA REQUIRES A PERMIT FOR INSTALLATION OF BOULEVARD TREES. SEE CITY OF MISSOULA STREET TREE ORDINANCE CITY MUNICIPAL CODE 12.32.

CLASS II TREE CLEARANCE REQUIREMENTS			
LOCATION	MINIMUM CLEARANCE		
ADJACENT TO SIDEWALK OR CURB	3' FROM CURB FACE OR SIDEWALK		
ADJACENT TO ANY BUILDING OR STRUCTURE	10' FROM BUILDING OR STRUCTURE		
ADJACENT TO METER BOXES AND PAD TRANSFORMERS	10' FROM METER VAULT BOX OR TRANSFORMER PAD		
RESIDENTIAL DRIVEWAYS	10' FROM RESIDENTIAL DRIVEWAY		
ALLEYWAYS	10' FROM ALLEYWAY		
FIRE HYDRANTS AND UTILITY POLES	10' FROM A HYDRANT OR UTILITY POLE		
SANITARY SEWER LATERAL	10' FROM SANITARY SEWER LATERALS		
STREET LIGHTS	20' FROM STREET LIGHTS		
TRAFFIC CONTROL SIGNS	25' IN FRONT OF TRAFFIC CONTROL SIGNS		
CORNER SIGHT TRIANGLE	30' FROM INTERSECTION RETURN		
DRAINAGE SUMP	10' FROM SUMP		

PLANT SCHEDULE

TREE KEY	QTY	BOTANICAL / COMMON NAME	SIZE	CONTAINER	COMMENTS
	25 EA	CELTIS OCCIDENTALIS X LAEVIGATA 'MAGNIFICA' MAGNIFICA HACKBERRY SPACING 30' O.C. OR AS SHOWN	2" CAL.	B&B	SINGLE-STEM
		OLUF LBERT D' O.C.		В&В	
		TILIA CORDATA 'G GREENSPIRE LITI DEN SPACING 30' O.C. VN		&B	:LL-BRANCHED, FULL CAI
		GLEDITSIA TRIAC TRUE SHADE HOI SPACING 30' O.C. VN		B&B	:LL-BRANGHED
300		TILIA AMERICANA AMERICAN LINDE SPACING 30' O.C.	2"		LL-BRANCHED, CENTRA
\bigcirc		GINKO BILOBA 'S, GINKO SARATOG SPACING 30' O.C. OR AS SHOWN		B&B	nk
0	21 EA	GYMNOCLADUS DIOICUS KENTUCKY COFFEE TREE SPACING 30'O.C. OR AS SHOWN	2" CAL.	B&B	WELL-BRANCHED




GRADING, BC


20

Р


9










HECTOR OF THOUSED TO SHOULD AND TRACT 2 OF C.O.S. 6817 HOWES SEC. 18. THAN, FINE WISSOULA LOFT HOWES SEC. 18. THAN, FINE WISSOULA LOFT HOWES SEC. 18. THAN, FINE WISSOULA COUNTY. SHEET: SHEET THE:								
MISSOULA LOFT HOMES NARY JANE BOULEVARD SEC. 18., T13N., R19W., P.M.M. ON MARY JANE SEC. 18., T13N., R19W., P.M.M. MISSOULA COUNTY MISSOULA M		PROJECT NO.	PROJECT NAME	LOCATION:		BEVISIONS	DATE	
SEC. 18, T13N, P.M.M. PREPARED FOR: MISSOULA COUNTY CI C		1		I HACL 5 AND LHACL 2 OF C.O.S. 6817 MARY JANE BOULEVARD	ESI RAI HEO		1	
PREPARED FOR: MISSOULA COUNTY OF 20 27 27 27 27 27 27 27 27 27 27 27 27 27		LO.00 / 00052	•	SEC. 18., T13N., R19W., P.M.M.	GN FTE CKE			
РРЕРАЯВЕ ГОЯ: MIRAMONTE 1817 SOUTH AVE. W. STE. A 1817 SOUTH AVE. W. STE. A 1817 SOUTH AVE. W. STE. A 1820 XX 1820 XX 1835 SOUTH AVE. W. STE. A 1835 SOUTH AVE. W. STE. A 1847 SOUTH AVE. W. STE. A 1858 SOUTH AVE. W. STE. A 1880 SOUTH AVE. W. STE. A 1886 SOUTH AVE. W. STE. A				MISSOULA COUNTY	EE D:			
MIRAMONTE		SHEET:	SHEET TITLE:	PREPARED FOR:	D: _ - : _ <u>A</u>			
10865	C	1000	GRADING, DRAINAGE, AND ROAD PLANS	MIRAMONTE	X, Do X, PR.,			1817 SOUTH AVE. W. STE. A PH: 406.721.0142
),	0 V	BOULEVARD TREE PLAN	HOMES	Y 0 Y 2023			
	0.007000	O/DESIGN/CIVIL\C3D/PLOT\PC	DAD(GRD-22000700.DWG					PLOT DATE: 6/12/2023 9:57 A












STORM WATER POLLUTION PREVENTION PLAN (SWPPP) NOTES


- 1. CONTRACTOR IS TO BE FAMILIAR WITH THE REQUIREMENTS OF SECTION 402(P) OF THE FEDERAL CLEAN WATER ACT AND REGULATIONS ADOPTED BY THE UNITED STATES ENVIRONMENTAL PROTECTION AGENCY (USEPA). (AMENDMENTS TO TITLE 40 OF THE CODE OF FEDERAL REGULATIONS, PART 122, PUBLISHED IN THE FEDERAL REGISTER ON NOVEMBER 16, 1990 AND ON APRIL 2, 1992.) ALSO, DEQ 1200-C PERMIT FOR THE CONTROL OF STORM WATER ASSOCIATED WITH CONSTRUCTION ACTIVITIES.
- 2. CONTRACTOR IS TO BE FAMILIAR WITH ALL REQUIREMENTS OF THE SWPPP.
- 3. ALL CONSTRUCTION SHALL BE IN ACCORDANCE WITH LOCAL JURISDICTION AND MONTANA DEQ FOR EROSION AND SEDIMENT CONTROL.
- 4. THE TEMPORARY POLLUTION CONTROL SYSTEM SHALL BE INSTALLED PRIOR TO ALL OTHER CONSTRUCTION.
- 5. ALL EQUIPMENT MAINTENANCE AND RE-FUELING SHALL BE CONDUCTED IN A SAFE MANNER AND SPILL KITS SHALL BE MAINTAINED ON-SITE TO CLEAN ANY SPILLS THAT MAY OCCUR.
- 6. ALL EXPOSED AND UNWORKED SOILS SHALL BE STABILIZED BY SUITABLE APPLICATION OF BEST MANAGEMENT PRACTICES (BMPS), SUCH AS VEGETATIVE COVER, MULCHING, PLASTIC COVERING OR APPLICATION OF GRAVEL SURFACES IN AREAS TO BE GRAVELED. NO EXPOSED AND UNWORKED SOILS SHALL REMAIN UNSTABILIZED. ONCE CONSTRUCTION ACTIVITY IS COMPLETED IN AN AREA BETWEEN THE MONTHS OF OCTOBER 1 AND APRIL 30, PERMANENT SEEDING SHALL BE INSTALLED.
- 7. THE CONTRACTOR IS RESPONSIBLE FOR DUST CONTROL AT ALL TIMES DURING CONSTRUCTION.
- 8. THE CONTRACTOR IS RESPONSIBLE FOR PROVIDING PROPER TRASH RECEPTACLES AND PORTABLE TOILETS ON-SITE AS WELL AS THE REGULAR MAINTENANCE OF THESE FACILITIES.
- 9, ALL CLEARING LIMITS AND/OR EASEMENT SETBACKS, SENSITIVE/CRITICAL AREAS AND THEIR BUFFERS, SIGNIFICANT TREES AND DRAINAGE COURSES SHALL BE CLEARLY STAKED AND MARKED AS SHOWN ON PLANS.
- 10. PROPERTIES ADJACENT TO THE PROJECT SITE THAT ARE SUBJECT TO POTENTIAL EROSION CAUSED BY CONSTRUCTION ACTIVITIES SHALL BE PROTECTED FROM SEDIMENT DEPOSITION THROUGH THE USE OF SILT FENCE. HAY BALES OR OTHER BMP SELECTED BY THE CONTRACTOR.
- 11. ALL FACILITIES INTENDED TO TRAP SEDIMENT ON-SITE SHALL BE CONSTRUCTED AS A FIRST STEP IN GRADING.
 THESE FACILITIES SHALL BE FUNCTIONAL BEFORE ANY LAND DISTURBING ACTIVITIES TAKE PLACE. EARTHEN STRUCTURES SUCH AS DAMS, DIKES AND DIVERSIONS SHALL BE SEEDED AND MULCHED ACCORDING TO THE TIME PERIOD STATED IN #6 ABOVE.


- 12. ALL CUT AND FILL SLOPES SHALL BE CONSTRUCTED IN A MANNER THAT WILL MINIMIZE EROSION. ALL SLOPES SHALL BE STABILIZED WITHIN THE TIME PERIOD STATED IN #6 ABOVE.
- 13. ALL STORM DRAINAGE INLETS MADE OPERABLE DURING CONSTRUCTION SHALL BE PROTECTED WITH A GRAVEL INTAKE FILTER TO PREVENT SEDIMENT FROM ENTERING THE SYSTEM. THE FILTER MUST BE INSPECTED REGULARLY AND CLEANED WHEN NECESSARY.
- 14. THE FOLLOWING SHALL APPLY TO CONSTRUCTION OF UTILITY LINES:
 - A. WHERE FEASIBLE, NO MORE THAN 500' OF TRENCH SHALL BE OPEN AT ONE TIME.
 - B. WHERE CONSISTENT WITH SAFETY AND SPACE CONSIDERATIONS, EXCAVATED MATERIAL SHALL BE PLACED ON THE UPHILL SIDE OF TRENCHES.
 - C. TRENCH DEWATERING DEVICES SHALL DISCHARGE AND SHALL REMAIN ON-SITE AND IN NO WAY ENTER PUBLIC PROPERTY OR WATERWAY.
- 15. WHEREVER CONSTRUCTION VEHICLE ACCESS ROUTES INTERSECT PAVED ROADS, A STABILIZED CONSTRUCTION ENTRANCE/EXIT SHALL BE CONSTRUCTED (SEE DETAIL SHEET) TO MINIMIZE THE TRANSPORT OF SEDIMENT (MUD) ONTO THE PAVED ROAD. IF SEDIMENT IS TRANSPORTED ONTO A ROAD SURFACE, THE ROADS SHALL BE CLEANED THOROUGHLY AT THE END OF EACH DAY. SEDIMENT SHALL BE REMOVED FROM ROADS BY SHOVELING OR SWEEPING AND BE TRANSPORTED TO A CONTROLLED SEDIMENT DISPOSAL AREA. STREET WASHING SHALL ONLY BE ALLOWED AFTER SEDIMENT IS REMOVED IN THIS MANNER. A MINIMUM OF ONE (1) ON-SITE STABILIZED CONSTRUCTION ENTRANCES SHALL BE INSTALLED.
- 16. CONCRETE TRUCKS SHALL NOT BE ALLOWED TO WASH OUT ON-SITE UNLESS A PROPERLY CONSTRUCTED CONCRETE TRUCK WASHOUT AREA IS CONSTRUCTED AND MAINTAINED.
- 17. ALL TRUCKS USED TO HAUL EXCAVATED SOILS FROM THE SITE SHALL BE INSPECTED AND SWEPT CLEAN OF
- 18. FUEL, LUBRICANTS AND OTHER FLUIDS REQUIRED FOR THE MAINTENANCE OF THE EQUIPMENT SHALL NOT BE
- 19. ALL TEMPORARY SEDIMENT AND EROSION CONTROL SHALL BE REMOVED WITHIN 30 DAYS AFTER FINAL SITE STABILIZATION IS ACHIEVED. TRAPPED SEDIMENT SHALL BE REMOVED OR STABILIZED ON-SITE. DISTURBED SOIL AREAS RESULTING FROM REMOVAL SHALL BE PERMANENTLY STABILIZED.
- 20. ALL POLLUTANTS OTHER THAN SEDIMENT THAT OCCUR ON-SITE DURING CONSTRUCTION SHALL BE HANDLED AND ISPOSED OF IN A MANNER THAT DOES NOT CAUSE CONTAMINATION OF STORM WATER OR THE SITE


- 21. ALL TEMPORARY AND PERMANENT EROSION AND SEDIMENT CONTROL FACILITIES SHALL BE INSPECTED, MAINTAINED AND REPAIRED BY THE CONTRACTOR AS NEEDED TO ASSURE CONTINUED PERFORMANCE OF THEIR INTENDED USE. ALL ON-SITE EROSION AND CONTROL MEASURES SHALL BE INSPECTED BY THE CONTRACTOR AT LEAST ONCE EVERY SEVEN (7) DAYS AND WITHIN 24 HOURS OF ANY STORM EVENT EQUAL TO OR GREATER THAN 0.25" OF RAIN PER 24 HOUR PERIOD. AN INSPECTION REPORT FILE SHALL BE MAINTAINED BY THE CONTRACTOR AND KEPT ON-SITE.
- 22. THE CONTRACTOR IS RESPONSIBLE TO PROVIDE ADDITIONAL TEMPORARY SEDIMENT PONDS/TRAPS AS SITE CONDITIONS REQUIRE. CONTRACTOR SHALL COORDINATE WITH THE ENGINEER.
- 23. THE CONTRACTOR IS RESPONSIBLE TO PROVIDE ADDITIONAL EROSION CONTROL MEASURES, INCLUDING BUT NOT LIMITED TO SILT FENCING. SEDIMENT PONDS/TRAPS, DIVERSION SWALES, CHECK DAMS, SEDIMENT BARRIERS, FILTER FABRIC MULCH AND SEEDING, AS CONDITIONS REQUIRE. THE CONTRACTOR SHALL
- 24. BMP'S TO LIMIT DISTURBANCE AND VEGETATIVE BUFFER AROUND LIMITS OF DISTURBANCE WHERE PRACTICAL.
- 25. CONTRACTOR TO PROVIDE SWPPP PACKET AND DEQ NOI CONFIRMATION LETTER TO CITY OF MISSOULA AND ACQUIRE CITY OF MISSOULA SWPPP PERMIT PRIOR TO ANY EARTH DISTURBING ACTIVITIES.
- 26. SWPPP INSPECTION RECORDS , NOT, AND NOT CONFIRMATION LETTER SHALL BE PROVIDED TO THE CITY OF MISSOULA AFTER THE PROJECT HAS REACHED FINAL STABILIZATION TO CLOSE OUT CITY
- 27. PUBLIC SIGNAGE IS REQUIRED PER SECTION 1.2.3 OF GENERAL PERMIT















REVISIO				
DESIGN	ED:	<i>x</i>	χ	
DRAFTE	D0			
CHECKE	D:		Х	
DATE:		APR.,	20.	2.
317	T			


TRACT 5 AND TRACT 2 OF C.O.S. 68
NARY JANE BOULEVARD
SEC. 18. T13N., R19W., P.M.M.
MISSOULA COUNTY MIRAMONTE HOMES


GRADING, DRAINAGE, AND ROAD PLANS ROAD CROSS SECTIONS MISSOULA LOFT HOMES ON MARY JANE


SHEET: 8 22000700.01
























DESIGNED: XX
DRAFTED: D0 CHECKED: XX DATE: APR., 2023 GRADING, DRAINAGE, AND ROAD PLANS CURRENT SHEET NAME MISSOULA LOFT HOMES ON MARY JANE 60





GENERAL NOTES:

vpical Utility Trench Detail

CONSTRUCTION MATERIALS AND PROCEDURES SHALL COMPLY WITH MONTANA PUBLIC WORKS STANDARD SPECIFICATIONS (MPWSS), 7TH EDITION, APRIL 2021, AS MODIFIED BY THE MISSOULA CITY PUBLIC WORKS STANDARDS AND SPECIFICATIONS MANUAL, APPENDIX 2-A (STANDARD MODIFICATIONS TO MEWES), CURRENT EDITION.

CASING PIPE (IF ANY) INSTALLED BY TRENCH CONSTRUCTION METHODS SHALL BE BEDDED AS SHOWN IN THIS DETAIL.





- SENSENTAL INCLES..

 CONSTRUCTION MATERIALS AND PROCEDURES SHALL COMPLY WITH MONTANA PUBLIC WORKS STANDARD SPECIFICATIONS (MPWSS), 7TH EDITION, APRIL 2021, AS MODIFIED BY THE MISSOULA CITY PUBLIC WORKS STANDARDS AND SPECIFICATIONS MANUAL, APPENDIX 2—A (STANDARD MODIFICATIONS TO MPWSS), CURRENT EDITION.


 COMBINATION CURB INLET FRAME AND GRATE SHALL BE USED WHERE INLET OR DRY WELL IS LOCATED IN TYPICAL "L"
- COMBINATION CURB INLET FRAME AND GRAIE SHALL BE USED WHENE INLET OR DRY WELL IS LOCATED IN TITIONAL INTERPRETABLE OF THE ACTION OF CASTINGS FOR EEDERALY FUNDED PROJECTS.
 DUE TO PROVISIONS IN THE INTERMODAL SUFFACE TRANSPORTATION ACT, VENDORS MUST AUTHENTICATE U.S. ORIGIN OF CASTINGS FOR FEDERALY FUNDED PROJECTS.
 VANED GRAITE (DAL 1-3559-04 OR APPROVED EQUAL) SHALL BE USED WHEN SLOPE EXCEEDS 5%.
 PROVIDE LIDS AND RINGS THAT MEET ANSTHO 3006 H20 LOADING RATING OR HIGHER.
 COMPOSITE TAPPERD GRADE RINGS SHALL BE USED TO MATCH FRAME & GRATE TO THE RUNNING SLOPE OF THE CURB.
 GRATE SHALL MATCH RUNNING SLOPE OF STREET.
 GRATE SHALL MATCH RUNNING SLOPE OF STREET.
 GRATE SHALL MATCH RUNNING SLOPE OF STREET.
 GROUT BOLT SLOTS LOCATED IN THE CURB LINE AND ALL OTHER OPENINGS TO BASE COURSE AND BACKFILL MATERIAL.

24" COMBINATION CURB INLET FRAME & GRATE

Utility Engineer

Adopted: 09 / 28 / 2020

STD - 601



The same and

- CONSTRUCTION MATERIALS AND PROCEDURES SHALL COMPLY WITH MONTANA PUBLIC WORKS STANDARD SPECIFICATIONS (MPWSS), 7TH EDITION, APRIL 2021, AS MODIFIED BY THE MISSOULA CITY PUBLIC WORKS STANDARDS AND SPECIFICATIONS
- MANUAL, APPENDIX 2-A (STANDARD MODIFICATIONS TO MPWSS), CURRENT EDITION.

 2. OVER-EXCAVATE WHERE REQUIRED TO ENSURE BOTTOM OF EXCAVATION IS A MIN. 2-FT INTO GRAVELLY SOIL.

 3. CATCH BASINS (STD-614) PIPED TO DRY WELLS ARE ENCOURAGED AS A PRE-TREATMENT METHOD OR TO AVOID UTILITY
- 4. NO GRADE RING TO BE OFFSET MORE THAN 2" AND TOTAL OFFSET NOT TO EXCEED WALL THICKNESS OF CONE.


Standard 8' Precast Dry Well

GRADE RINGS SHALL BE 2" THICKNESS MINIMUM.
 NO WEDGES ALLOWED BETWEEN GRADE RINGS AND FRAME MUST BE SET FLUSH WITH TOP GRADE RING.

Approved By Utility Engineer

Adopted: 09 / 28 / 2020

STD - 616




CONSTRUCTION MATERIALS AND PROCEDURES SHALL COMPLY WITH MONTANA PUBLIC WORKS STANDARD SPECIFICATIONS (MPWSS), 7TH EDITION, APRIL 2021, AS MODIFIED BY THE MISSOULA CITY PUBLIC WORKS STANDARDS AND SPECIFICATIONS MANUAL, APPRIDIX 2—A (STANDARDS MODIFICATIONS TO MPWSS), CURRENT EDITION.

Utility Engineer

Adopted: 11/15/2021

STD - 617

Standard Remote Dry Well




KEYED NOTES:

- (1) 2" 12 GAUGE TELESPAR® PERFORATED STEEL SOUARE TUBING SIGN POST, OR CITY ENGINEER APPROVED EQUIVALENT, SHALL B USED FOR ALL SIGN INSTALLATIONS UPON/MITHIN THE RIGHT-OF-WAY (UNLESS SIGN AREA (50-FT) EXCEEDS YIELD ACCORDING TO AASHTO STANDARD SPECIFICATIONS FOR STRUCTURAL SUPPORTS). TELESPAR ®OR EQUAL MATERIAL SPECIFICATIONS: STEEL CONFORMING TO ASTM A-1011 GRADE 50 AND GALVANIZING CONFORMING TO ASTM A-653.
- ② SET SIGN FLUSH WITH OR ABOVE TOP OF POST, TOP OF SIGN SHALL NOT BE PLACED BELOW TOP OF POST, SIGN SHOULD BE FULLY SUPPORTED BY POST.
- 3 FASTEN SIGN POST TO THROUGH-DRILLED ANCHOR SLEEVE WITH 5/16" X 3" GRADE 2 BOLT WITH FLAT WASHERS AND NYLON-INSERT LOCK NUT. PLACE BOLT 1" BELOW THE TOP OF ANCHOR SLEEVE.
- (4) GALVANIZED 2-1/2" X 2-1/2" X 18" LONG (MIN.), 7 GAUGE NON-PERFORATED STEEL SQUARE TUBING ANCHOR SLEEVE

GENERAL NOTES:

- ALL SIGNS SHALL COMPLY WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), MOST CURRENT VERSION, REVISION AND / OR SUPPLEMENT, FOR SIGN MATERIAL(S), SIZE, THICKNESS, SHAPE, COLOR(S), MESSAGE, SYMBOLOGY AND RETRICREFECTIVITY.
- 2. ALL SIGNS LOCATED UPON/WITHIN THE PUBLIC RIGHT-OF-WAY SHALL BE SLEEVE-MOUNTED FOR BREAKAWAY AND REPLACEABILITY.
- FINAL SIGN LOCATION AND / OR PLACEMENT SHALL BE IN ACCORDANCE WITH THE MUTCO AND AS DETERMINED AND APPROVED BY THE CITY ENGINEER OR SIGN SHOP SUPERVISOR.
- 2-1/2" 12 GAUGE SHALL BE USED FOR LARGER SIGN AREA INSTALLATIONS. THE CITY ENGINEER MAY REQUIRE ALTERNATE SIZES, GAUGES, ETC, BASED ON SIGN SURFACE AREA.




STREET NAME SIGN MATERIAL SPECIFICATIONS:


- ALUMINUM BLANKS 6" X 18", 24", 30", 36" X .08"
- 2. MARKINGS SHALL BE PLACED ON ONE SIDE OF SIGN ONLY.

- TEXT SIZE SPECIFICATION:
 3.1. 4" INITIAL UPPERCASE.
 3.2. 3" NOMINAL LOOP LOWERCASE NOT INCLUDING ASCENDING AND/OR DESCENDING TAIL. 3.3. 2" BLOCK NUMBER. 3.4. 2" ROUTE DESIGNATION — ALL CAPS — CENTER WITH BLOCK NUMBER.
- 4. TWO SIGNS SHALL BE MOUNTED BACK TO BACK ON EITHER SIDE OF THE SIGN POST. 2 SIGNS ARE REQUIRED.
- 5. GREEN BACKGROUND WITH WHITE TEXT FOR PUBLIC STREETS.
- 6. WHITE BACKGROUND WITH GREEN TEXT FOR PRIVATE STREETS.

STREET NAME SIGN MATERIAL AND SPACING SPECIFICATIONS:

- ALL STREET NAME SIGNS SHALL COMPLY WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), MOST CURRENT VERSION, REVISION AND/OR SUPPLEMENT, FOR SIGN MATERIAL(S), SIZE, THICKNESS, SHAPE, COLOR(S), MESSAGE, SYMBOLOGY AND RETROFELECTIVITY.
- FINAL STREET NAME SIGN LOCATION AND/OR PLACEMENT SHALL BE IN ACCORDANCE WITH THE MUTCD AND AS DETERMINED AND APPROVED BY THE CITY ENGINEER OR SIGN SHOP SUPERVISOR.
- 3. SPACING BETWEEN EACH SIGN ON A SINGLE POLE SHALL BE NO GREATER THAN 1" AND MUST NOT OVERLAP
- 4. ALL OTHER SIGNS SHALL DEFAULT TO MUTCD STANDARDS AND SPECIFICATIONS.






KEYED NOTES:

- (1) IMPERVIOUS FILL MATERIAL (FOR CURB WITH BOULEVARD): SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02528
- 3) SUBBASE COURSE: SEE TABLE 7-4 IN MCPWSS AND CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02234
- 4. SUBGRADE: SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02230 & 02528
- G GUTTER PANS SHALL BE 8 INCHES MINIMUM THICKNESS FROM PC TO PT AT COLLECTOR AND ARTERIAL MITERSECTIONS, ROUNDABOUTS AND SPLITTER ISLANDS, THROUGH COMMERCIAL AND INDUSTRIAL APPROACHES, OR WHERE TRUCK TRAFFIC IS ASSUMED.

Typical "L" Type Curb/Gutter Section



GENERAL NOTES:

- SEE CITY OF MISSOULA STD-740 FOR BASE, SUB BASE, SUB GRADE, FILL MATERIAL, AND EIGHT (8") INCH THICKNESS REQUIREMENTS.
- "B" TYPE CURB IS SUITABLE FOR SMALL REPLACEMENT SECTIONS WITH "B" CURB ON EITHER END OF THE REPLACEMENT SECTION OR USED FOR LANDSCAPE RETAINING CURB.



ypical Boulevard Sign Base

Public Right-of-Way

Adopted: 01/27/1999 Revised: 01/01/2023

STD - 720

Typical Street Name Sign Standard

Adopted: 0.3 / 15 / 2006 STD - 721

- France

Adopted: 01/30/1980 Revised: 01/01/2023 STD - 740 Typical "B" Type Curb Section

Adopted: 04/09/1973 Revised: 01/01/2023 City Engineer

STD - 743



U

DESIGNED: XX

CHECKED: XX

APR., 2023

MIRAMONTE HOMES

PLANS

ROAD

DRAINAGE, AND DETAIL SHEET

GRADING,

60


D8

LOFT HOME ARY JANE

MISSOULA I

DATE:

FAX:



- (2) BASE COURSE. SEE CITY OF MISSOULA MODIFICATIONS TO MPWSS SECTIONS 02235 AND 02529
- (3.) SUBGRADE. SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02230
- 4. SHOULDER. SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02529
- 5. CONTRACTION JOINTS. SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02529
- (6.) EXPANSION JOINTS. SEE CITY OF MISSOULA MODIFICATION TO MPWSS SECTION 02529
- (5) ISOLATION JOINTS. FOR USE AROUND OBJECTS WITHIN OR PROTRUDING FROM SIDEWALK (E.G. AROUND MANHOLES LIDS, VALVE BOXES, UTILITY POLES, HYDRANTS, POLE BASES, ETC.)
- (8) SLEEVE. TYP 4" SCH 40 PVC. MUST BE BELOW BASE AND IN SUBGRADE. EXTEND 6" BEYOND EDGE OF SIDEWALK. STAMP
 "S" IN THE FINISH SURFACE DIRECTLY ABOVE THE SLEEVE AT BOTH EDGES OF SIDEWALK.






Approved By City Engineer

Adopted:02/29/1996 Revised: 01/01/2023 STD - 752

STD - 651



Temporary Gravel Construction Entrance

A TEMPORARY GRAVEL CONSTRUCTION ENTRANCE SHALL BE LOCATED AT POINTS OF VEHICULAR EGRESS ON A CONSTRUCTION SITE TO LIMIT THE AMOUNT OF SEDIMENT TRANSPORTED ONTO PUBLIC ROADS BY VEHICLES.

PREMOVE AND REPLACE AGGREGATE WHEN VOIDS ECOME FILLED.

SWEEP AND REMOVE SEDIMENT TRACKED ONTO PAVED SURFACES.

PROPERTY GRADE INGRESS/EGRESS POINTS TO PREVENT RUNOFF FROM LEAVING THE SITE.

CONSIDER THE USE OF RUMBLE PADS, FODS, OR CATTLE GUARDS IN COMBINATION WITH THE GRAVEL CONSTRUCTION ENTRANCE TO IMPROVE EFFECTIVENESS

NONWOVEN GEOTEXTILE FABRIC -


GENERAL NOTES:

Approved By Utility Engineer Andy Schultz, PE


20' RADIUS -


ised: 09/28/2020

STD - 650



Approved By Utility Engineer Andy Schultz, PE





A CONCRETE WASHOUT AREA DETAIL

NOT TO SCALE

D

DATE	
REVISIONS	
DESIGNED: XX DRAFTED: D0 CHECKED: XX DATE: APR., 202.	-

PLAN GRADING, DRAINAGE, AND ROAD DETAIL SHEET MISSOULA LOFT HOMES ON MARY JANE

60

60